

MXP7000

TETRA AND LTE PORTABLE DEVICE

YOUR APPS. YOUR COMMS. YOUR TEAM. TOGETHER

MISSION-CRITICAL CONVERGED TETRA AND LTE PORTABLE DEVICE

The MXP7000 provides versatile communications. It delivers mission-critical TETRA and 4G LTE broadband voice and data communications, in a secure and rugged Android device.

It's easy to use and operate the MXP7000. The large push-to-talk button lets users connect instantly, and the field-swappable battery helps them stay connected longer. Innovative audio technology enables your personnel to hear and be heard clearly, even in noisy and windy conditions. It has a 5-inch touchscreen and the device can run applications for optimal workforce productivity.

The MXP7000 is easy to deploy and manage, and it supports Bluetooth® 5.1 for data transfer. It has a GCAI-mini connector, so you can provide your teams with accessories tailored to their needs.

No matter their mission, the MXP7000 is a device that helps your teams get the job done.



GENERAL SPECIFICATIONS

SOFTWARE	
Operating System	Android 11 Non-GMS
HARDWARE	
Dimensions	Height: 210mm (with antenna) Height: 150mm (without antenna) Width: 80mm Depth: 29.85mm (with battery)
Weight	440g (with battery and antenna)
Battery Options	5600mAh IMPRES™ 2
Housing Colour	Black Green (selected models)
Display	5.0", 1280 x 720 Capacitive, touch-screen with Corning® Gorilla® glass Supports use with disposable and combat gloves
Controls	Large Push-to-talk button Emergency button Dual function rotary knob 2 configurable side buttons
Memory	4GB RAM 64GB Internal Storage Supports microSD
SIM Slots	TETRA SIM: 2FF (Mini SIM) LTE: 4FF (Nano SIM)
Camera	Rear 13MP, with integrated flash Front 8MP
Video Recording Quality	1080p at 60 fps
Sensors	Proximity Ambient Light Accelerometer Barometer Gyroscope E-Compass
Ports	GCAI-mini USB-C

DEVICE SECURITY

User Authentication	PIN or password
Key Storage	Hardware-backed encryption with Trusted Execution Environment (TEE)
Trusted Boot Process	Included with the use of tamper resistant hardware
OS Hardening	Android OS hardening and SELinux access control
Auditing	Auditing / logging functionality, with security logs captured and stored in a secured manner
Data-at-Rest	Using Android's AES256 File Based Encryption
Data-in-Transit	Encryption with IPSec VPN support
Secured Device Management	With the use of Integrated Terminal Management (iTM) solution
Restricted Recovery Mode	Included to avoid unauthorised access to features

AUDIO

Audio Power at Rated	2W
Audio Distortion at Rated	<1%
Audio Power at Maximum	3W
Max loudness	99Phon
Noise supression	Adaptive Multi-Microphone Beam-Forming
Number of Microphones	3 dedicated + 1 loudspeaker as microphone

TETRA SERVICE

RF	
Frequency Bands	380-430MHz
Transmitter RF Power	Class 3L (1.8W) Class 4 (1W)
Adaptive Power Control	Per EN 300 392-2
Receiver Class	A and B
Receiver Static Sensitivity	-116dBm (guaranteed) -118dBm (typical)
Receiver Dynamic Sensitivity	-107dBm (guaranteed) -109dBm (typical)

DMO REPEATER	
	ETSI type 1A DMO repeater for channel efficient operation
	Repeats DMO voice and tone signalling on selected talkgroup
	Repeats SDS and status messaging on selected talkgroup
DMO Repeater Mode Features and Functions	Transmission of repeater presence signal
	Emergency Call (Pre-emptive Priority Call)
	Monitoring of and participation in calls whilst in repeater mode

DATA	
	Status messaging in TMO and DMO
Short Data	SDS messaging in TMO and DMO Supports concatenated SDS (1000 characters)
	Short data applications

VOICE	
Full Duplex Call	TMO: Private, emergency
Half Duplex Call	TMO: Private, group, emergency
	DMO: Private, group, emergency
	Non-Tactical: Emergency group call to dedicated talkgroup
Emergency Call Management (user customisable)	Individual: Emergency call to pre-defined party (half/full duplex) Hot Mic: Allows user to talk without needing to press PTT button Emergency alert
	Emergency status message to dispatch console
	Gateway
	Repeater
Other Voice Functions	Repeater mode PTT double push
	Pre-emptive priority calls

SECURITY	
Authentication	Infrastructure initiated and made mutual by radio terminal
Air Interface Encryption - Algorithms	TEA 1, TEA 2, TEA 3
Protocols - Security Classes	Class 1 (Clear) Class 2 (SCK) Class 3 (DCK/CCK, OTAR-CCK, OTAR-SCK) Class 3G (GCK, OTAR-GCK)
End-to-End Encryption	SIM based encryption including BSI
	Temporary disable (stun)
Other Security Features	Permanent disable (either ETSI standard or customer restorable)



CONNECTIVITY

TETRA ANTENNA	
Connector	SMA
Impedance	Impedance 50 Ω
LTE / 3G / 2G	
LTE Bands	B3, B7, B20, B28
3G Bands	B1, B8
2G Bands	900MHz, 1800MHz
WI-FI	
IEEE Standards Supported	802.11 a/b/g/n/ac
Wi-Fi Bands	2.4GHz and 5GHz
BLUETOOTH	
Bluetooth Versions Supported	Bluetooth 5.1 (data transfer only)
Bluetooth Profiles	Generic Attribute (GATT) Attribute Protocol (ATT) Generic Access Profile (GAP) Serial Port Profile (SPP) Personal Area Networking Profile (PAN) Object Push Profile (OPP) Headset Profile (HSP)

LOCATION SERVICES

Constellation Supported	GPS, aGPS, Galileo, GLONASS, BDS (BeiDou)
GNSS Antenna	Internal antenna
GNSS Tracking Sensitivity	GPS: -158dBm (50% Fix losses) -162dBm (typical)
Horizontal Accuracy, 2D	<5m (95% probable, -130dBm)
TTF Cold Start	<60 sec (95% probable at -130dBm)
Protocols	ETSI LIP (short and long), Motorola Solutions LRRP

KEY FEATURES & SETTINGS

DEVICE	
Airplane Mode ¹	Turns ON/OFF Mobile Data, Wi-Fi and Bluetooth simultaneously
Location	Turns ON/OFF location functionality
Sound	Media volume Radio & voice calls Ring & notification volume Alarm volume
Night Vision Goggle (NVG) Mode	Turn ON to set the display luminance for use with night vision goggles. LEDs will be turned OFF when in NVG mode
Display Brightness Level	Manual and Automatic brightness adjustment
Flashlight	Toggle LED flashlight ON / OFF
TETRA	
Talkgroup Management	User friendly, flexible, fast and efficient interface
Talkgroups	TMO folders: up to 256, TMO talkgroups: up to 10000 DMO folders: up to 128, DMO talkgroups: up to 2000
Favourite Talkgroup Folders	Up to 3
Contacts Management	Rapid search to find the contact easily
Contacts	Up to 1000 contacts
Multiple Dialling Methods	Dialling direct, scroll and select via touchscreen
Call Alert	Vibrate alert and set ringtones via Android Settings
Fall Alert (Man-down)	Triggers an emergency alert if the device is continuously tilted beyond a pre-defined angle
Message Management	Distinct folders for each message type for flexible message management
Text Message List	Up to 200 entries (short messages) At least 20 entries for outbox (long messages up to 1000 characters) At least 10 entries for inbox (long messages up to 1000 characters)
Status List	Up to 100 user-defined messages Assignable to One Touch Buttons
Text Entry	Touchscreen for ease of use
Transmit Inhibit	Disables TETRA transmit and puts device into Airplane Mode

¹ TETRA communications is still available



DEVICE MANAGEMENT SOLUTIONS

Integrated Terminal Management (iTM) Supports iTM version 8.0 onwards

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature ²	-20°C to +60°C
Storage Temperature	-40°C to +85°C
Humidity (High) , Low and High Temperature	ETSI 300 019-1-7 class 7.3E
Shock (bumps & shock), vibration (random)	ETSI 300-019 1-7 class 5M3
Dust and Water Ingress Protection	Black model: IP68 per IEC 60529 Green model: IP67 per IEC 60529
Compliance to US Military Standard 810	See table to the right

² Performance may be limited when operating at extreme temperatures.

US MILITARY STANDARD MATRIX

	MIL STD 810H	
	Method	Proc/Cat
Low Pressure	500.6	II
High Temperature	501.7	I/A1,II
Low Temperature	502.7	I,II
Thermal Shock	503.7	I-C
Solar Radiation	505.7	I/A1
Humidity	507.6	II / Aggravated
Salt Fog	509.7	-
Blowing Sand	510.7	II
Vibration	514.8	I/Cat 24,II/Cat 5
Shock ³	516.8	I,IV,VI

³ Drop test is covered as part of Shock Method 516.8 Proc IV, VI

For more information, please visit us at
motorolasolutions.com/mxp7000

Motorola Solutions UK Limited, Nova South, 160 Victoria Street, London, SW1E 5LB.

All specifications are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under licence. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Motorola Solutions, Inc. is under licence. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved. (09-23)